

POLYCARBONATE RESIN COMPOSITION CONTAINING TITANIUM DIOXIDE AND SULFONE SULFONATE SALT

5 FIELD OF THE INVENTION

The present invention relates to polycarbonate resin compositions having excellent light reflectance and impact resistance. More particularly, the present invention relates to titanium dioxide-containing polycarbonate resin compositions which also contain at least one sulfone sulfonate salt.

10

BACKGROUND OF THE INVENTION

In general, a liquid crystal display (LCD) is composed of an LCD panel portion and a backlight unit. The LCD panel portion is composed of a glass substrate, a transparent electrode, liquid crystal and a color filter, and the backlight unit is composed of a reflector for providing backlighting, a fluorescent lamp, a light guide panel, a diffusion sheet, a prism sheet and a backlight frame. The backlight unit is made of a polymer resin. The backlight unit should have high light reflectance to reflect the backlights without loss and good fluidity and impact strength to carry out effectively the function of the frame, and have a thin thickness. In addition, the backlight unit should have good heat resistance, dimensional stability and flameproof resistance. Polycarbonate is an exemplary polymer material that has the above characteristics.

Polycarbonate resin has been widely used as an engineering plastic for automobiles and electrical appliances because the resin has good impact strength, self-extinguishing properties, dimensional stability, transparency, mechanical strength, and heat resistance. However, unlike other conventional impact resistant resins, the impact strength of the polycarbonate resin is sensitive to the molecular weight of the polycarbonate, circumstances of use, notch impact, residual stress, etc. Furthermore, because the polycarbonate resin has a lower fluidity than other thermoplastic resins, it requires a high molding temperature during the molding process. Accordingly the high temperature causes thermal degradation of the polycarbonate resin, resulting in reduction of the molecular weight. Also, in order to compensate for lower fluidity, high injection pressure and high injection speed have been applied to the resin in the injection molding process. This process provides a certain part of a molded article with significant residual

stress. Thermal degradation and residual stress can deteriorate the impact strength of the molded article. In addition, the impact strength is affected by other factors such as use of the molded article at high temperature and exposure of the molded article to a chemical. In other words, under these circumstances, the impact strength deteriorates. Accordingly, the practical use of polycarbonate resin is narrowly limited.

To minimize loss of the backlights in an LCD, the polycarbonate resin is quite often applied to the backlight frame by coloring in pure white. To prepare such pure white polycarbonate resin with high reflectance, US Patent No. 5,837,757 discloses a flame retardant polycarbonate resin composition comprising a polycarbonate resin and a titanium oxide powder in a ration by weight of from 70/30 to 90/10 and containing a compound containing the stilbene-bisbenzoxazole group. However, the polycarbonate resin composition cannot provide a high reflectance of 90 % or above. Further, the composition has shortcomings in big drop of heat resistance and impact strength, because the polycarbonate is degraded by the titanium oxide.

In Japanese Patent Laid-open No. 9-176471, the impact strength of a molded article is also greatly decreased because a large amount of titanium oxide degrades the polycarbonate resin. Japanese Patent Laid-open No. 7-242781 discloses a resin composition having an increased impact resistance by adding styrene or metacryl resin that contain a diene rubber, but the reflectance is decreased because the rubber is color-changed by a long time exposure at high temperature.

Accordingly, the present inventors have developed a new polycarbonate resin composition having good reflectance and appearance in pure white color by employing titanium dioxide, and adding at least one sulfone sulfonate salt which prevents decrease in impact strength. The resin compositions may also contain an optional impact strength reinforcing material to inhibit degradation of the polycarbonate resin.

SUMMARY OF THE INVENTION

The polycarbonate resin composition having good reflectance and impact strength according to the present invention comprises (A) about 100 parts by weight of a thermoplastic polycarbonate resin as a base resin, (B) about 2-20 parts by weight of titanium dioxide, (C) about 0.01-5 parts by weight of a sulfone sulfonate salt or mixture of sulfone sulfonate salts, optionally

(D) about 0-30 parts by weight of an impact modifier, (E) optionally about 0-30 parts by weight of a vinyl copolymer, and optionally (F) about 0-1.0 parts by weight of a stilbene-bisbenzoxazole derivative.

The present invention provides a polycarbonate resin composition having good reflectance by employing titanium dioxide and at least one sulfone sulfonate salt. The compositions according to the present invention have excellent light reflectance, good impact strength, and high fluidity and can be used in the reflector or frame of the backlight unit of liquid crystal displays for notebook computers, monitors, television sets, camcorders and digital cameras. The resin composition is particularly useful for the production of a backlight frame of an LCD.

Another feature of the present invention is the provision of a polycarbonate resin composition having good impact strength by containing a polycarbonate resin, titanium dioxide, at least one sulfone sulfonate salt and optionally an impact strength reinforcing material, a vinyl copolymer, and/or a stilbene-bisbenzoxazole derivative.


These and other features and advantages of the present invention will be apparent from the ensuing disclosure.

DETAILED DESCRIPTION OF THE INVENTION

(A) Polycarbonate Resin

The polycarbonate resin for use in this invention is known in the art such as in U.S. 5,837,757, herein incorporated by reference. The polycarbonate resin can be prepared by conventional methods which are well known to an ordinary skilled person in the art. The use of such a resin in a thermoplastic resin composition is also well known.

The polycarbonate resin (A) in the present invention is prepared by reacting a diphenol represented by the following formula (I) with a phosgene, a halogen formate or a carboxyldiester:



wherein A is C₁-C₃ alkylene, C₁-C₃ alkylidene, C₅-C₆ cycloalkylidene, S or SO₂ conjugated by a single bond.

The diphenols represented by the formula (I) include hydroquinone, resorcinol, 4,4'-dihydroxydiphenyl, 2,2-bis(4-hydroxyphenyl)propane, 2,4-bis(4-hydroxyphenyl)-2-methylbutane, 1,1-bis(4-hydroxyphenyl)cyclohexane, 2,2-bis(3-chloro-4-hydroxyphenyl)propane, 2,2-bis(3,5-dichloro-4-hydroxyphenyl)propane etc. Bisphenols such as 2, 2'-bis(4-hydroxyphenyl)propane, 1,1-bis(4-hydroxyphenyl)cyclohexane, and 2,2-bis(3,5-dichloro-4-hydroxyphenyl)propane are preferred and 2,2-bis(4-hydroxyphenyl)propane called "Bisphenol A" is most preferred.

The weight average molecular weight of the polycarbonate resin (A) of the present invention is preferably about from 10,000 to 200,000, and more preferably about from 15,000 to 80,000. Polycarbonates useful in the present invention may be branched in a known manner, namely by the incorporation of 0.05 to 2 mol%, relative to the total amount of diphenols used, of trifunctional or greater than trifunctional compounds, for example such compounds with three or more phenolic groups. Further, an aromatic polyester-carbonate resin that is prepared by polymerization in the presence of an ester precursor such as difunctional carboxylate may be replaced for some or all of the polycarbonate resin.

In the present invention, the polycarbonate resin may be a homopolymer or a copolymer of diphenols, or mixtures thereof.

Further, an aromatic polyester-carbonate resin that is prepared by polymerization in the presence of an ester precursor such as difunctional carboxylate may be used in place of some or all of the polycarbonate resin.

The polycarbonate resin is used in the amount of about 100 parts by weight as a base resin.

(B) Titanium Dioxide

Various types of titanium dioxide are known in the art. Titanium dioxide is classified into Anatase type and Rutile type depending on crystallization. Titanium dioxide is classified into various types depending on shape of particle, surface treating agent to be used and average size of particle. Any type of titanium dioxide can be used in the present invention. However, it is

preferable to use Rutile type with a median particle size of about 0.15-0.25 to obtain good reflectance and mechanical properties.

The titanium dioxide is used in the amount of about 2-20 parts by weight, preferably about 8-12 parts by weight, per 100 parts by weight of the base resin (A)


5

(C) Sulfone Sulfonate Salt

The sulfone sulfonate salt for use in this invention include alkyl or aromatic sulfone sulfonate salts, and mixtures thereof. Suitable sulfone sulfonate salts are disclosed in U.S. 3,948,851, herein incorporated by reference. Alkali metal salts and alkali earth metal salts are preferably used. Sodium, lithium, potassium, rubidium, cesium, beryllium, magnesium, calcium, strontium or barium salts are suitable.

10

The sulfone sulfonate salt is represented by the following formula (II):



15

where X is an electron withdrawing radical; M is an alkali or an alkali earth metal; and R' and R'' are respectively an aryl radical having one or two of an aromatic ring or an aliphatic radical of C₁-C₆, and may be the same or different. Suitable X radicals include halo, nitro, trihalomethyl, and cyano radicals. Aromatic sulfone sulfonate salts are preferred.

20

Sulfone sulfonate salts that can be used in the present invention include potassium diphenylsulfone-3-sulfonate, dipotassium diphenylsulfone-3,3'-disulfonate, potassium 4-chloro-3'-(trifluoromethyl)diphenylsulfone-3-sulfonate, sodium diphenylsulfone-3-sulfonate, sodium 4,4'-dibromodiphenylsulfone-3-sulfonate, disodium diphenylsulfone-3,3'-disulfonate and disodium 4,4'-dichlorodiphenylsulfone-3,3'-disulfonate.

25

The sulfone sulfonate salt is used in the amount of about 0.01-5 parts by weight, preferably about 0.05-2 parts by weight, most preferably about 0.05-0.5 parts by weight per 100 parts by weight of the base resin (A).

(D) Impact Modifier

The polycarbonate composition according to the present invention may optionally include a graft copolymer, an olefin copolymer or mixtures thereof as an impact strength reinforcing material also referred to as an impact modifier.

30

The graft copolymer useful as an impact modifier is prepared by polymerizing at least one monomer selected from the group consisting of an acrylate monomer or a silicone monomer, and then by grafting at least one monomer selected from the group consisting of a styrene, α -methylstyrene, a halogen- or alkyl-substituted styrene, an acrylonitrile, a methacrylonitrile, a C₁-C₈ alkyl acrylate, a C₁-C₈ alkyl methacrylate, a maleic anhydride, and a C₁-C₄ alkyl- or phenyl-substituted maleimide. The amount of the rubber is preferably from about 20 to 90 parts by weight per the graft copolymer. Preferably, a graft copolymer prepared by grafting styrene or acrylonitrile monomers onto silicon monomers is used.

Suitable examples of the acrylate monomers include propyl acrylate, butyl acrylate, 2-ethylhexyl acrylate, hexyl acrylate, and 2-ethylhexyl acrylate. In the acrylate rubber, a crosslinking agent such as ethylene-glycol dimethacrylate, propylene-glycol dimethacrylate, 1,3-butylene glycoldimethacrylate, 1,4-butylene glycoldimethacrylate, allyl methacrylate, and triallyl cyanurate may be used.

Examples of silicone monomers include cyclosiloxanes such as hexamethyl cyclotrisiloxane, octamethyl cyclotetrasiloxane, decamethyl cyclopentasiloxane, dodecamethyl cyclohexasiloxane, trimethyl triphenylcyclotrisiloxane, tetramethyl tetraphenyl cyclotetrasiloxane, and octaphenyl cyclotetrasiloxane. In the polymerization of the silicon monomer, a crosslinking agent may be employed such as trimethoxy methylsilane, triethoxy phenylsilane, tetramethoxy silane, and tetraethoxy silane.

The graft copolymer is prepared by a conventional process such as emulsion polymerization, suspension polymerization, solution polymerization or bulk polymerization which is well known to an ordinary skilled person in the art. Preferably, emulsion or bulk polymerization is employed by adding vinyl monomers to rubber polymers using an initiator.

An olefin copolymer suitable for use as an impact modifier can be prepared by at least one olefin monomer selected from the group consisting of ethylene, propylene, isopropylene, butylene, and isobutylene. The olefin copolymer is prepared by using a Ziegler-Natta catalyst or a metallocene catalyst. For preparing an olefin copolymer with a desirable structure, it is preferable to use a metallocene catalyst. For improving the dispersability of the olefin copolymer in the polycarbonate, a functional monomer can be grafted onto the olefin copolymer to form functional groups. A maleic anhydride is preferably used as a functional monomer.

The impact modifier is used in the amount of about 0-30 parts by weight, preferably about 1-5 parts by weight per 100 parts by weight of the base resin (A).

(E) Vinyl Copolymer

A vinyl copolymer may optionally be included in the polycarbonate resin composition according to the present invention. The vinyl copolymer is prepared by polymerizing at least one unsaturated monomer selected from the group consisting of a styrene, an α -methylstyrene, a halogen- or alkyl-substituted styrene, an acrylonitrile, a methacrylonitrile, a C_1 - C_8 alkyl acrylate, a C_1 - C_8 alkyl methacrylate, a maleic anhydride, an alkyl- or phenyl-substituted maleimide of C_1 - C_4 , and the mixtures thereof. It is preferable to polymerize at least one monomer selected from the group consisting of a styrene, a methacrylate methyl ester, and an acrylonitrile.



The C_1 - C_8 alkyl methacrylate are esters of a methacrylic acid, and a C_1 - C_8 alkyl acrylate are esters of an acrylic acid. The C_1 - C_8 alkyl methacrylate and C_1 - C_8 alkyl acrylate are monohydric alcohols of C_1 - C_8 . The examples of C_1 - C_8 alkyl methacrylate include methacrylic acid methylester, methacrylic acid ethylester, and methacrylic acid propylester.

Vinyl copolymer suitable for use in the present invention are prepared by emulsion polymerization, suspension polymerization, solution polymerization or melt polymerization. It is preferable to use a vinyl copolymer with weight average molecular weight about from 15,000 to 200,000.

Mixtures of vinyl copolymers may also be used. The vinyl copolymer is employed in the amount of about 0-30 parts by weight, preferably less than or equal to about 3 parts by weight per 100 parts by weight of the base resin (A).

(F) Stilbene-bisbenzoxazole Derivative

The stilbene-bisbenzoxazole derivatives can optionally be used in the compositions according to the invention and function to increase the reflectance of the polycarbonate resin composition. Examples of the stilbene-bisbenzoxazole derivatives include 4-(benzoxazole-2-yl)-4'-(5-methylbenzoxazole-2-yl) stilbene of the following formula (III) and 4,4'-bis(benzoxazole-2-yl) stilbene of the following formula (IV):



The stilbene-bisbenzoxazole derivative can be used together with a pigment such as blue and violet in an appropriate amount. A commercial product can be used. The stilbene-bisbenzoxazole derivative is used in the amount of about 0-1.0 parts by weight, preferably about 0.01-0.3 parts by weight, and most preferably 0.01-0.05 parts by weight as per 100 parts by weight of the base resin (A).

The polycarbonate resin composition according to the present invention may include additives such as an inorganic filler, an ultraviolet stabilizer, a heat stabilizer, an antioxidant, a flame retardant, a lubricant, a pigment, a dye and the mixtures thereof in order to improve the physical properties such as mechanical strength and heat distortion temperature. Preferred examples of the inorganic filler are glass fiber, carbon fiber, talc, silica, mica, alumina etc.

The resin composition according to the present invention is prepared in a form of pellet by extruding the blend with a conventional extruder.

The invention is illustrated in the following Examples which are intended for the purpose of illustration and are not to be construed as in any way limiting the scope of the present invention.

EXAMPLES

Components (A) polycarbonate resin, (B) titanium dioxide, (C) sulfone sulfonate salt, (D1) graft copolymer resin 1, (D2) graft copolymer resin 2, (E) styrene-acrylonitrile (SAN) copolymer, and (F) stilbene-bisbenzoxazole derivative in Examples 1-8 and Comparative Examples 1-4 are described as follows:

(A) Polycarbonate resin

A "Bisphenol A" type linear polycarbonate was used. The weight average molecular weight is about from 20,000 to 30,000.

5 (B) Titanium Dioxide

Sub
C7

Rutile titanium dioxide with a median particle size of about 0.15 - 0.25 μ m was used.

(C) Sulfone Sulfonate Salt

10 A mixture of potassium diphenylsulfone-3-sulfonate and dipotassium diphenylsulfone-3,3 disulfonate in the ratio by weight of 75 : 25 was used. The content of diphenylsulfonate by product was less than 0.3% by weight.

(D) Impact Modifier

(D1) Graft copolymer resin 1

15 Graft copolymer resin 1 (SRK-200 (grade name) from Mitsubishi Rayon Co.) was prepared by grafting styrene and acrylonitrile monomers onto silicone rubber.

(D2) Graft copolymer resin 2

20 Twelve parts by weight of acrylonitrile and 33 parts by weight of styrene monomers were grafted onto 55 parts by weight of polybutadiene rubber latex with an average particle diameter of about 0.3 μ m through a conventional emulsion process to prepare graft copolymer resin 2. The graft ratio of the copolymer is in the range of about 55 %.

(E) Styrene-Acrylonitrile Copolymer (SAN copolymer)

25 Seventy parts by weight of styrene and 30 parts by weight of acrylonitrile were put into 120 parts by weight of deionized water, and 0.2 parts by weight of azobisisobutyronitrile and 0.5 parts by weight of tricalciumphosphate were added to the mixture. Styrene-acrylonitrile copolymer was prepared by suspension polymerization, followed by washing, dehydrating, and drying. The styrene-acrylonitrile copolymer was obtained in powder form.

F) Stilbene-bisbenzoxazole Derivative

The stilbene-bisbenzoxazole derivative used in these examples was 4-(benzoxazole-2-yl)-4'-(5-methylbenzoxazole-2-yl) stilbene. Pigment Blue was added to the stilbene-bisbenzoxazole derivative.

The amounts of the components used in Examples 1-8 and Comparative Examples 1-4 are shown in Table 1.

TABLE 1

Components	Examples								Comparative Examples			
	1	2	3	4	5	6	7	8	1	2	3	4
Polycarbonate (A)	100	100	100	100	100	100	100	100	100	100	100	100
Titanium Dioxide (B)	10	10	10	10	10	10	10	10	10	10	10	10
Sulfone sulfonate salt (C)	0.1	0.1	0.1	0.1	0.5	0.5	2	4	-	-	-	-
Graft copolymer 1 (D1)	-	-	5	5	-	-	5	-	-	-	-	5
Graft copolymer 2 (D2)	-	-	-	-	-	5	-	-	-	5	5	-
SAN copolymer (E)	-	-	-	5	-	5	5	-	-	5	5	5
Stilbene derivative (F)	-	0.01	0.01	0.01	-	-	0.01	0.01	-	-	0.01	0.01

As shown in Table 1, the components were blended, and then an antioxidant and a heat stabilizer were added and mixed. The resultant was fed into a twin-screw extruder of L/D 29 and $\Phi = 45\text{mm}$. The resin compositions were prepared in pellet form by extruding the blend with the extruder.

The resultant pellets were dried at 110 °C for over 3 hours and were injection-molded. The test specimens (64mm x 12.7mm x 3.2mm) for measuring Izod impact strength and the test specimens (127mm x 127mm x 2mm) for observing falling impact were prepared. The Notched Izod impact strength for each Example and Comparative Example was tested in accordance with ASTM D256, and the reflectance was measured with injection- molded specimens (9cm x 5cm) by using a spectrophotometer by Minolta Co. To measure the change of reflectance by heat, the reflectance was measured with the same specimens, after being at 100 °C for 500 hours, by using the same method. The Notched Izod impact strength and reflectances at different wavelengths for each Example and Comparative Example are shown in the following Table 2.

10

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205

TABLE 2

5		Examples								Comparative Examples			
		1	2	3	4	5	6	7	8	1	2	3	4
	Notched Izod Impact Strength (kgf · cm/cm)(1/8")	60	60	70	60	60	58	60	58	10	55	50	56
10	Reflectance (%)												
	At 450 mm	90.6	99.0	99.1	99.5	90.7	91.2	99.6	99.3	80.4	83.6	95.4	96.1
	At 500 mm	90.8	96.9	96.9	97.0	90.8	91.4	97.1	97.0	82.4	86.8	93.2	93.9
	At 550 mm	91.0	96.0	96.0	96.2	91.3	91.8	96.4	96.2	85.5	89.0	89.2	89.9
	At 600 mm	91.7	96.0	96.1	96.5	91.8	92.3	96.6	96.3	86.8	90.7	90.5	91.1
15	At 650 mm	91.9	96.5	96.5	96.5	92.0	92.4	96.7	96.5	87.3	91.9	91.4	92.0
	At 700 mm	92.9	97.1	97.1	97.0	92.9	93.2	97.1	97.0	88.7	92.9	92.5	93.2
	Lowest Reflectance	90.6	96.0	96.0	96.2	90.8	91.2	96.4	96.2	80.4	83.6	89.2	89.9
20	Reflectance after 500 hrs at 100 °C (%)												
	At 450 mm	89.6	96.0	96.2	96.5	89.8	89.8	96.3	96.1	79.2	78.5	85.1	86.0
	At 500 mm	89.7	95.9	96.1	96.5	89.9	89.9	96.4	96.2	81.5	81.6	86.3	87.2
	At 550 mm	90.1	95.5	95.7	96.0	90.3	90.3	95.8	95.5	84.7	84.8	85.5	86.5
25	At 600 mm	90.7	95.8	95.9	96.2	90.8	90.8	96.0	95.8	86.2	86.7	86.6	87.5
	At 650 mm	91.0	96.0	96.2	96.3	91.2	91.2	96.1	96.0	87.0	87.6	87.7	88.7
	At 700 mm	92.1	96.5	96.8	96.8	92.3	92.3	96.5	96.3	88.1	89.2	89.3	90.2
	Lowest Reflectance	89.6	95.5	95.7	96.0	89.8	89.8	95.8	95.5	79.2	78.5	85.1	86.0

As shown in Table 2, the resin compositions of Comparative Examples 1 - 4 which do not contain sulfone sulfonate salt (C) show large drops in impact strength and much lower reflectances than the compositions of Examples 1 - 8.

5 It is apparent from the above that many modifications and changes and use of equivalent components and amounts are possible without departing from the spirit and scope of the present invention.